

Nutshell Natural Paints Ltd. Unit 3, Leigham Units Silverton Road, Matford Park Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Revision: 1.1 2010-01-25

Email: enquiries@nutshellpaints.co.uk

NUTSHELL Floor & Furniture Wax

Product NUTSHELL Floor & Furniture Wax will protect and nourish your furniture and all interior wood,

terracotta and stone surfaces, giving a natural wax seal. When polished, this wax gives a subtle, satin finish which is water and dirt resistant. Wood becomes lightly honey-coloured, stone slightly

darker.

Ingredients Ingredients: beeswax, boiled linseed oil, balsam terpinol, carnauba wax, larch resin, a mixture of

natural essential oils, lead-free drying agents. NUTSHELL Floor & Furniture Wax is hand produced

by warming and blending well proven natural materials.

Coverage Coverage approximately 20-40 ml per sq. metre, depending on the surface.

Areas of use NUTSHELL Floor & Furniture Wax is suitable for use on all types of interior wood, including floors,

doors, furniture, toys, etc., and for the restoration of previously waxed surfaces.

NUTSHELL Floor & Furniture Wax contains larch resins and a high proportion of beeswax, which makes the consistency of the product extremely soft and easy to work with, while giving a pleasant scent and finish. The presence of carnauba wax makes NUTSHELL Floor & Furniture Wax suitable for harder wearing surfaces like floors, shelves and tables, and it dries to a hard wearing finish. However, for heavily used softwood floors we recommend the use of NUTSHELL Tuf Wood Wax And Tuf Wood Oil.

NUTSHELL Floor & Furniture Wax is not suitable for areas where there is standing water. For work-tops, window sills etc., we recommend the use of NUTSHELL Herb and Resin Oil or

NUTSHELL varnishes.

Size Available in 400g tins.

Preparation The surface must be clean, dry and grease free. Wood can first be sanded with fine sandpaper

and wiped clean. Surfaces that are very absorbent should be primed with NUTSHELL Herb & Resin

Oil, which must be allowed to dry completely.

Application A thin, sticky layer may develop on top of the wax inside the tin. This does not affect the quality

of the product but should be removed with a spatula. Warm the wax if it is cold, by placing the

tin in a bowl of hot water. Take care as wax is flammable.

Apply the wax thinly and evenly with a lint free cloth. For floors, the use of a polishing machine is recommended. Polish after 2-4 hours with a dry cloth or brush. This will bring up the satin sheen, which indicates that the density of the surface layer is developing. After a day, another polish may follow; the more the wax is polished, the denser and better wearing the surface

becomes.

Drying Time Floors may be carefully walked on after the first polishing, but all newly waxed and polished

surfaces should be used with care for several days, while total hardening takes place.



Nutshell Natural Paints Ltd. Unit 3, Leigham Units Silverton Road, Matford Park Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Revision: 1.1 2010-01-25

Email: enquiries@nutshellpaints.co.uk

NUTSHELL Floor & Furniture Wax

Thinning & Cleaning

N/A

Aftercare

Freshly waxed floors should be waxed regularly in the first few weeks, so that a stable and easy-to-clean wax layer is built up. Little used areas, such as the edges of floors, may be exempt. Add a little NUTSHELL Maintenance Lotion to the cleaning water. Use coasters for hot pots and cups on waxed surfaces.

Liming wax & other coloured waxes

NUTSHELL Floor & Furniture Wax may be blended with NUTSHELL Earth & Mineral Pigments to give a variety of interesting and original finishes on wood. We suggest for Liming wax, use white, for Antique Pine use Yellow Ochre, for Mahogany use Sienna Red.

The wax should be carefully warmed in a non-flammable container using hot water, and pigment worked into the wax. Alternatively, wax on a cloth can be dabbed into the pigment before applying it. Please remember that wax is flammable and care must be taken.

Storage & Handling

Store in a cool, frost free place.

This product is flammable. Do not smoke whilst working with this product or use near a naked flame. Air rooms thoroughly. Saturated polishing rags should be kept in a closed container to avoid the danger of spontaneous combustion. Always close lid firmly and store well out of reach of children

Safety

- Store well away from children and pets.
- Avoid skin and eye contact. Wash eyes immediately with plenty of water if contact should occur.
- Ensure good ventilation.
- Close lid firmly after use.
- Store and use away from heat and flame.
- Do not eat in the vicinity of work.
- Wash hands after use.

The information given in this Technical Information Sheet and any technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact Nutshell Paints at the address shown above. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.