

# Technical Information Sheet

---



Nutshell Natural Paints Ltd.  
Unit 3, Leigham Units  
Silverton Road, Matford Park  
Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Email: [enquiries@nutshellpaints.co.uk](mailto:enquiries@nutshellpaints.co.uk)

## NUTSHELL Super Eco Emulsion *plus*

Revision: 1.4 2010-02-05

<b>Product</b>	This is a water based, opaque, washable emulsion for interior use on concrete, plaster, plasterboard and wood. It has good covering power, is easy to work with, covers and fills well, and allows for splatter free application. Matt finish.
<b>Ingredients</b>	Contains: titanium dioxide, chalk, talc, cellulose, beeswax, phosphate, sodium hydroxide and an inert in-can preservative. It contains no formaldehyde, petrochemicals or VOCs.
<b>Coverage</b>	Coverage is approximately 8 - 10 sq. metres per litre. Coverage will vary considerably depending on method of application, surface roughness, weather conditions and complexity of structure.
<b>Areas of use</b>	Suitable for use indoors on concrete, plaster, plasterboard, all mineral surfaces, wood, wood chip paper etc. where a washable finish is required. Not suitable for cob, lime washed walls or new plaster.
<b>Size</b>	Available in 2.5 litre and 5 litre tins.
<b>Preparation</b>	All surfaces should be clean, free from grease, oil and dust. Thoroughly remove water-soluble chalk, paint or lime washes. Roughen old lacquer, vinyl silk, gloss and oil paints by light sanding. All loose and flaking paints must be removed. Very sandy or friable surfaces will require a compatible sealer (for example NUTSHELL Herb & Resin Oil). Any areas of algae or fungal growth should be treated with an acceptable fungicidal wash.
<b>Application</b>	Apply with a brush or short pile roller. Apply evenly. Two coats may be required on absorbent surfaces. On very porous, friable surfaces a compatible sealer will be required (for example NUTSHELL Herb & Resin Oil).
<b>Drying Time</b>	Substrate temperature 20°C  Touch dry 1-2 hours. Recoat after 4 hours. Paint will be fully hardened after 10 days. Drying/curing times will be shortened by higher temperatures and lengthened by lower temperatures.
<b>Thinning &amp; Cleaning</b>	Thin and clean with water. Clean tools with soap and water immediately after use.
<b>Storage &amp; Handling</b>	Store in a cool, but definitely frost free place, in a well closed container. Always keep container closed and out of reach of children. NUTSHELL Super Eco Emulsion <i>plus</i> is biodegradable, but PLEASE do not pour the remainder down the drain.  Flash point: Non flammable Product Density: 1.33 kg/litre Shelf Life: Approximately 6 months if opened otherwise about 2 years in unopened containers in a frost free store



Nutshell Natural Paints Ltd.  
Unit 3, Leigham Units  
Silverton Road, Matford Park  
Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Email: [enquiries@nutshellpaints.co.uk](mailto:enquiries@nutshellpaints.co.uk)

## NUTSHELL Super Eco Emulsion *plus*

Revision: 1.4 2010-02-05

Volume Solids: 33%

### Safety

- As with all paints store well away from children and pets.
- Avoid skin and eye contact. Wash eyes immediately with plenty of water if contact should occur.
- Ensure good ventilation.
- Close lid firmly after use.
- Store and use away from heat and flame.
- Do not eat in the vicinity of work.
- Wash hands after use.

The information given in this Technical Information Sheet and any technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact Nutshell Paints at the address shown above. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.