



Nutshell Natural Paints Ltd.  
Unit 3, Leigham Units  
Silverton Road, Matford Park  
Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Email: [enquiries@nutshellpaints.co.uk](mailto:enquiries@nutshellpaints.co.uk)

## NUTSHELL Super Eco Emulsion

Revision: 1.1 2010-01-25

<b>Product</b>	This is a water based, opaque, emulsion paint, for interior use on concrete, plaster, plasterboard, mineral surfaces and wood. It has good covering power, is easy to work with, covers and fills well, and allows for splatter free application. The finish is matt.
<b>Ingredients</b>	Contains: titanium dioxide, chalk, talc, cellulose, beeswax, phosphate, sodium hydroxide and an inert in-can preservative. It contains no formaldehyde, petrochemicals or VOCs.
<b>Coverage</b>	Coverage is approximately 8 - 10 sq. metres per litre. Coverage will vary considerably depending on method of application, surface roughness, weather conditions and complexity of structure.
<b>Areas of use</b>	Suitable for use indoors on concrete, plaster, plasterboard, all mineral surfaces, wood, wood chip paper, wallpaper etc.
<b>Size</b>	Available in 2.5 litre and 5 litre tins.
<b>Preparation</b>	All surfaces should be clean, free from grease, oil and dust. Thoroughly remove water-soluble chalk, paint or lime washes. Roughen old lacquer, vinyl silk, gloss and oil paints by light sanding. All loose and flaking paints must be removed. Very sandy or friable surfaces will require a compatible sealer (for example NUTSHELL Herb & Resin Oil). Any areas of algae or fungal growth should be treated with an acceptable fungicidal wash.
<b>Application</b>	NUTSHELL Super Eco Emulsion should be applied by brush or short pile roller. Apply evenly. Two coats may be required on absorbent surfaces such as new plaster, sandstone, etc. On very porous, friable surfaces a compatible sealer will be required (for example NUTSHELL Herb & Resin Oil). For maximum opacity use as supplied; it can be thinned with up to 10% water for use on absorbent surfaces.
<b>Drying Time</b>	Substrate Temperature: 20°C  Touch dry: 1-2 hours, can be recoated after 4 hours. Paint will be finally hardened after 10 days. Drying/ curing times will be shortened by higher temperatures and lengthened by lower temperatures. Material and freshly applied paint must be protected from frost.
<b>Colouring</b>	May be tinted using NUTSHELL Earth and Mineral pigments. Stir the pigment powder with a little water or the paint from the tin to form a smooth lump-free paste, leave to soak, and then add to tin and stir thoroughly before use.
<b>Thinning &amp; Cleaning</b>	Thin and clean with water.
<b>Storage &amp; Handling</b>	Store in a cool, but definitely frost free place, in a well closed container. Always keep container closed and out of reach of children. NUTSHELL Super Eco Emulsion is biodegradable, but PLEASE do not pour the remainder down the drain.



Nutshell Natural Paints Ltd.  
Unit 3, Leigham Units  
Silverton Road, Matford Park  
Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Email: [enquiries@nutshellpaints.co.uk](mailto:enquiries@nutshellpaints.co.uk)

## NUTSHELL Super Eco Emulsion

Revision: 1.1 2010-01-25

Flash point: Non flammable

Product Density: 1.44 kg/litre

Shelf Life: Approximately 6 months if opened otherwise about 2 years in unopened containers in a frost free store.

Volume Solids: 33%

### Safety

- As with all paints store well away from children and pets.
- Avoid skin and eye contact. Wash eyes immediately with plenty of water if contact should occur.
- Ensure good ventilation.
- Close lid firmly after use.
- Store and use away from heat and flame.
- Do not eat in the vicinity of work.
- Wash hands after use.

The information given in this Technical Information Sheet and any technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact Nutshell Paints at the address shown above. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.