



Nutshell Natural Paints Ltd.  
Unit 3, Leigham Units  
Silverton Road, Matford Park  
Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760  
Fax: +44 (0) 1392 824 437

Email: [enquiries@nutshellpaints.co.uk](mailto:enquiries@nutshellpaints.co.uk)

## NUTSHELL Tuf Wood Wax

Revision: 1.1 2010-01-25

<b>Product</b>	NUTSHELL Tuf Wood Wax is an open-porous, transparent finish for wood, cork and ceramic (terracotta) applications with pads or rags. Do not apply with a brush as it is too thick. It is made of renewable resources. The Wax is particularly good for wood or cork floors, stairs, window sills etc. Although the product contains wax it can be sanded in case of later renovation.
<b>Ingredients</b>	Carnauba Wax, Balsam turpin oil, orange peel oil, linseed stand oil, castor oil, concentrated colophony stand oil, cobalt, manganese, zirconium and lead free zinc dryer.
<b>Coverage</b>	Coverage is approximately 20-40 ml per sq. metre Actual consumption depends on processing and the surface to which it is to be applied.
<b>Areas of use</b>	For the treatment of interior floors and surfaces.
<b>Size</b>	Available in 0.75 litre and 2.5 litre tins.
<b>Preparation</b>	The surface should be primed with Tuff Wood Oil and be clean, dust free, and thoroughly dried. Remove contamination and dust with a damp cloth.
<b>Application</b>	Do not process under 14C. Stir thoroughly before using. Processing order: The undercoat must be completely dry. Apply by polishing the area thinly with a rag or single-disc polishing pad. Let to dry for 8 - 24 hours then polish with a dry rag, brush or machine.  Tip: Depending on the climate, surface and type of application, the correct timing for polishing is different. On cork it can be much quicker. Polishing should be easy with no smearing. Do not leave too long as product can not be polished when it is thoroughly dried.  Tip: Worn parts of the area can be renovated with Tuf Wood Wax.
<b>Drying Time</b>	Can be polished after approximately. 8 - 24 hours, use carefully after 48 hours. Longer waiting time for cork surfaces. Use the surface carefully before hardening after 1 - 4 weeks.
<b>Thinning &amp; Cleaning</b>	N/A
<b>Storage &amp; Handling</b>	Saturated cleaning rags should be stored in a closed container to prevent the possibility of spontaneous combustion. Or soak the rag in water and let it dry. On Contact with the skin or eyes, clean quickly with soap and plenty of water. Do not smoke or use an open light whilst working and air rooms thoroughly. Wear respiratory protection when spraying the product. Also keep ecological paints away from children. Product is classified as irritant (XI) because of the content of natural essential oils.

Warning Category: Vbf A 3, inflammable, irritant.



Nutshell Natural Paints Ltd.  
Unit 3, Leigham Units  
Silverton Road, Matford Park  
Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Email: [enquiries@nutshellpaints.co.uk](mailto:enquiries@nutshellpaints.co.uk)

## NUTSHELL Tuf Wood Wax

Revision: 1.1 2010-01-25

### Safety

- Store well away from children and pets.
- Avoid skin and eye contact. Wash eyes immediately with plenty of water if contact should occur.
- Ensure good ventilation.
- Close lid firmly after use.
- Store and use away from heat and flame.
- Do not eat in the vicinity of work.
- Wash hands after use.

The information given in this Technical Information Sheet and any technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact Nutshell Paints at the address shown above. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.